

Model	PD220V-II
Series	PD Series
Interface	RS232/ USB
Display Method	Vacuum Fluorescent Display (Blue-green)
Number of characters	40 (20 columns* 2 lines)
Brightness	500~1000 cd/m2
Character font	5* 7 dot matrix
Character type	95 Alphanumeric, 32 International Characters
Character size	9.02(H)* 5.25(W)mm
Dot Size (X* Y)	0.86* 1.05mm
Download characters	9 characters
Pole Dimension	Per support length: 140(L)* 34.5(Dia)mm
Viewing Aangle	Max. 60°
Horizontal Rotation	Max. 355°
Command Mode	LD220,EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	FRENCH, DEUTSCH, ENGLISH, DENISH, SWISS, ITALIAN, SPANISH, JAPANESE, SLAVONIC, RUSSIAN, PORTUGUESE, CANADIAN, CANADIAN, NORDIC, TURKISH, GREEK, WEST EUROPEAN LATIN, CP858, CP860, WPC1252, CP857 (TURKISH), POLISH,WPC1250,WPC1253, (GREEK), WPC1255 (HEBREW) , WPC1251, CP866, CP852, CP737 (GREEK) CP858, CP864 (ARABIC), FARSI (IRAN)
Connection	Baud rate direct connection 9600 or 19,200 bps

Reliability	MTBF 30,000 hours
Consumption	5~24V DC
Panel Dimension	20(W)* 7.8(D)* 3.1(H)cm
Base Dimension	17(W)* 9.9(D)* 3.9(H)cm
Minimum Height	15.5cm
Maximum Height	41.5cm
Net Weight	0.83kg
Packing Dimension	28*23*8cm
Gross Weight	1.1kg