

| | | |
|-----------|---------------------------|---|
| Parameter | Model | S8360-UL |
| | Interfaces | USB+LAN |
| | Print Method | Direct Line Thermal |
| | Print Comand | ESC / POS command |
| | Print Speed | 220mm/s |
| | Resolution | 203DPI (8dot/mm) |
| | TPH Reliability | 100km |
| | Auto Cutter | Partial |
| | Cutter Life | 1 million cuts |
| | Logo | support downloading and printing logo |
| | Line Spacing | 3.75mm (Adjustable by commands) |
| | Extension Character Sheet | PC437 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、Thai、PT151 (1251) |
| | Character Size | ANK, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese:3.0×3.0mm (24×24 dots) |
| | Supported Code: | 1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR CODE,PDF417 |

| | | |
|---------|-------------------|---|
| | Input Buffer | 96K bytes |
| | NV Flash | 256K bytes |
| | Driver | Win2003 / WinXP / Win7 / WIN8 / WIN10/ Win11 Linux / IOS / Android |
| | Power | Input : AC 110V/220V, 50~60Hz ; Output : DC 24V/2.5A |
| Paper | Paper Types | Thermal Roll Paper |
| | Paper Width | 79.5±0.5mm / φ 80 mm |
| | Print Width | 72mm |
| | Paper Thickness | 0.06-0.08 mm |
| Package | Printer Dimension | 17.5*14.2*12.2 CM |
| | Printer N.W. | 0.84kg |
| | Accessories | Manual, USB Cable, Power Adapter, Paper Roll |
| | Box Dimension | 19.8*18.4*13.9 CM |
| | Box G.W. | 1.22 Kgs |