

Model	S6400E
Operating Mode	Bluetooth (Bluetooth HID/ Bluetooth SPP/ Bluetooth BLE)
	2.4G
	USB
Image Sensor	CMOS
Pixels	640*480 CMOS
Battery Capacity	2000mAh
Memory	16Mb
Storage Capacity	≥130000pieces (EAN13)
Floodlight	White LED
Reading code system- 1D	EAN-8, EAN-13, UPC-E, UPC-A, ISBN, ISSN, Code128, Code 39, Code 93, Code 11, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5, Industrial 25, Standard 25, Plessey, MSI-Plessey
Reading code system- 2D	QR Code、 Micro QR, Data Matrix, PDF417
Accuracy	≥5mil
Scan Angle	Pitch $\pm 55^{\circ}$ @ $0^{\circ}$ Roll and $0^{\circ}$ Skew
	Roll $\pm 360^{\circ}$ @ $0^{\circ}$ Pitch and $0^{\circ}$ Skew
	Skew $\pm 55^{\circ}$ @ $0^{\circ}$ Roll and $0^{\circ}$

	Pitch	
Contrast ratio	≥20%	
Reading Depth of Field	1D EAN13 5mil 45~130mm	
	1D EAN13 13mil 45~230mm	
	QR code 15mil 19~170mm	
	QR code 30mil 30~260mm	
Operating Current	200mA	
Standby Current	54mA	
Sleep	0mA	
Notification	Beep, LED indicator	
Physical	Product size	15.2*10.7*6.5cm
	Product weight	175g
	Package size	20.5*11*8cm
	Package weight	305g (with accessories)
Environmental	Operating Temperature	-20°C~+60°C
	Storage Temperature	-40°C~+70°C
	Humidity	5%~95% (non-condensing)

2.